



ELEMENT

Motorcycle Trailer

Specifications vary by plant



STANDARD FEATURES

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 24" O.C. Roof Bows
- Spring Axles
- EZ-Lube Hubs
- 4-Wheel Electric Brakes
- 15" Radial Tires
- 2-5/16" Coupler
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- V-Front
- 24" Polished Aluminum on Bottom Exterior Sides & Rear
- Aluminum Exterior
- 1 Piece Aluminum Roof
- 24" Stoneguard
- Ramp Door with Spring Assist & 12" Ramp Door Extension
- 32" Entry Door with Flushlock
- (2) Sidewall Vents
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- (1) Dome Light and Switch
- Beavertail
- (6) Pieces Floor E-Track
- (2) Wheel Chocks
- Automotive Undercoating
- Limited 3 Year Warranty



Shown with optional vinyl interior

ELEMENT MOTORCYCLE

	EWLM7X12TE2	EWLM7X14TE2	EWLM7X16TE2
Overall Length	16'6"	18'6"	20'6"
Width	102"	102"	102"
Height	84"	84"	84"
Interior Length	13'4"	15'4"	17'4"
Interior Width	78 1/2"	78 1/2"	78 1/2"
Interior Height	66"	66"	66"
Platform Height	17"	17"	17"
Rear Opening Ht.	66"	66"	66"
Rear Opening Wd.	76 1/2"	76 1/2"	76 1/2"
Hitch Ball Height	16"	16"	16"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"
Brakes	ELECTRIC	ELECTRIC	ELECTRIC
GVWR	7000#	7000#	7000#
Hitch Weight	234#	265#	348#
Curb Weight	2050#	2210#	3160#
Payload Capacity	4950#	4790#	3840#
Tires	15"	15"	15"
Wheels	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"
Sidewalls	High Performance Wall Liner	High Performance Wall Liner	High Performance Wall Liner
Tail Lights	LED	LED	LED
Clearance Lights	LED	LED	LED
Dome Light	1	1	1
Switch	STD	STD	STD
Sidewall Vents	2	2	2
Stone Guard	24"	24"	24"
V-Nose	STD	STD	STD
Side Door	32"	32"	32"
Ramp	STD	STD	STD
Sand Pad	STD	STD	STD
Crossmembers	24" OC	24" OC	24" OC
Side Posts	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive

Specifications Subject to Change Without Notice