



# ELEMENT SE

## 5', 6' & 7' Wide Cargo Trailers

Specifications vary by plant.  
Available in select regions only.



### STANDARD FEATURES

May be shown with optional equipment

- Tube Main Frame Construction
- 16" O.C. Floor Construction
- 16" O.C. Sidewall Construction
- 24" O.C. Roof Construction
- Spring Axles
- EZ-Lube Hubs
- 15" Radial Tires
- 2000# Tongue Jack
- 24" Flat Top Slope V-Nose on 5' and 6' Wides
- 30" Flat Top Slope V-Nose on 7' Wides
- Sand Pad
- 1 Piece Aluminum Roof
- 2" Coupler (Single Axle)
- 2-5/16" Coupler (Tandem Axle)
- 4-Way Plug (Single Axle)
- 7-Way Plug (Tandem Axle)
- Safety Chains
- .030 Aluminum Screwless Exterior
- LED Tail Lights
- LED Clearance Lights
- ATP Fenders
- ATP Slanted Stoneguard
- ATP Nose
- 3/4" High Performance Floor
- High Performance Sidewalls
- (1) 12V LED Dome Light w/ Switch
- (2) Sidewall Vents
- 32" Aluminum Framed Side Door w/Flush Lock (6' & 7' wides)
- Aluminum Framed Double Rear Doors
- Single Rear Door on 5' Wides
- Automotive Undercoating
- Limited 3 Year Warranty

	<b>ELEMENT SE CARGO</b>								
	EWLC 5X8S12	EWLC 5X10S12	EWLC 6X10S12	EWLC 6X12S12	EWLC 6X12TE2	EWLC 7X12SE2	EWLC 7X12TE2	EWLC 7X14TE2	EWLC 7X16TE2
Overall Length	12'3"	14'3"	14'3"	16'3"	16'3"	16'3"	16'3"	18'3"	20'3"
Width	82"	82"	93"	93"	93"	102"	102"	102"	102"
Height	86"	86"	92"	92"	93"	93"	93"	93"	93"
Interior Length	115.5"	139.5"	140"	164"	164"	167"	167"	191"	215"
Interior Width	56"	56"	68"	68"	68"	80"	80"	80"	80"
Interior Height	66"	66"	72"	72"	72"	72"	72"	72"	72"
Platform Height	18"	18"	18"	18"	19"	19"	19"	19"	19"
Rear Opening Height	60"	60"	66"	66"	66"	66"	66"	66"	66"
Rear Opening Width	51"	51"	66"	66"	66"	77 ½"	77 ½"	77 ½"	77 ½"
Hitch Ball Height	18"	18"	18"	18"	19"	19"	19"	19"	19"
Hitch Ball Size	2"	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Brakes	OPT	OPT	OPT	OPT	STD	STD	STD	STD	STD
GVWR	2990#	2990#	2990#	2990#	7000#	3500#	7000#	7000#	7000#
Hitch Weight	125#	138#	154#	171#	218#	212#	241#	260#	274#
Curb Weight	1035#	1148#	1285#	1430#	1820#	1770#	2012#	2168#	2280#
Payload Cpty.	1955#	1842#	1705#	1560#	5180#	1730#	4988#	4832#	4720#
Tires	15"	15"	15"	15"	15"	15"	15"	15"	15"
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance
Tail Lights	LED	LED	LED	LED	LED	LED	LED	LED	LED
Clearance Lgt.	LED	LED	LED	LED	LED	LED	LED	LED	LED
Stone Guard	STD	STD	STD	STD	STD	STD	STD	STD	STD
Dome Light	1	1	1	1	1	1	1	1	1
Switch	STD	STD	STD	STD	STD	STD	STD	STD	STD
Sidewall Vents	2	2	2	2	2	2	2	2	2
Side Door	OPT	OPT	32"	32"	32"	32"	32"	32"	32"
Rear Door	SINGLE	SINGLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE
Sand Pad	STD	STD	STD	STD	STD	STD	STD	STD	STD
Crossmembers	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES	YES	YES	YES	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive

Specifications Subject to Change Without Notice