



VISION

Cargo
5' & 6' Wide

Specifications vary by plant

**Now a
5 Year
Warranty**



STANDARD FEATURES

Optional Equipment May Be Shown

- Tube Main Frame Construction
- 16" O.C. Frame
- 16" O.C. Tube Sidewalls
- 24" O.C. Roof Bows
- Spring Axles
- EZ-Lube Hubs
- 15" Radial Tires
- Chrome Plastic Hub Caps
- 2" Coupler (Single Axle)
- 2-5/16" Coupler (Tandem Axle)
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- 24" Bullnose (Flat Top)
- Radius Front (Round Top)
- TPO Cap (Round Top)
- .080 Top Wrap (Round Top)
- .030 Screwless Aluminum Exterior
- Chrome Corners or Nose
- 1 Piece Aluminum Roof
- Aluminum Fenders
- 24" Stoneguard
- Ramp Door w/ Spring Assist or Double Rear Doors
- Entry Door w/ Flushlock
- (2) Sidewall Vents
- 4-Way Plug (Single Axle)
- 7-Way Plug (Tandem Axle)
- LED Tail Lights
- LED Clearance Lights
- LED Fender Mount Turn Signals
- (2) LED Dome Lights w/ Switch
- Automotive Undercoating
- Limited 5 Year Warranty

	VISION CARGO						
	VRLC5X8SI2	VRLC5X10SI2	VRLC6X10SI2	VRLC6X12SI2	VRLC6X12TE2	VRLC6X14SI2	VRLC6X14TE2
Overall Length	11'11"	13'11"	13'11"	15'11"	15'11"	17'11"	17'11"
Width	81"	81"	93"	93"	93"	93"	93"
Height	87"	87"	93"	93"	93"	93"	93"
Interior Length	8'4"	10'4"	10'4"	12'5"	12'5"	14'5"	14'5"
Interior Width	56"	56"	68"	68"	68"	68"	68"
Interior Height	66"	66"	72"	72"	72"	72"	72"
Platform Height	18"	18"	18"	18"	18"	18"	18"
Rear Opening Ht.	60"	60"	66"	66"	66"	66"	66"
Rear Opening Wd.	51"	51"	66"	66"	66"	66"	66"
Hitch Ball Height	18"	18"	18"	18"	18"	18"	18"
Hitch Ball Size	2"	2"	2"	2"	2 5/16"	2"	2 5/16"
Brakes	OPT	OPT	OPT	OPT	STD	OPT	STD
GVWR	2990#	2990#	2990#	2990#	7000#	2990#	7000#
Hitch Weight	131#	142#	161#	179#	192#	200#	225#
Curb Weight	1050#	1155#	1290#	1415#	1800#	1545#	1970#
Payload Capacity	1940#	1835#	1700#	1575#	5200#	1445#	5030#
Tires	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance	High Performance
Tail Lights	LED	LED	LED	LED	LED	LED	LED
Clearance Lights	LED	LED	LED	LED	LED	LED	LED
Dome Light	2	2	2	2	2	2	2
Switch	STD	STD	STD	STD	STD	STD	STD
Sidewall Vents	2	2	2	2	2	2	2
Stone Guard	24"	24"	24"	24"	24"	24"	24"
Side Door	OPT	OPT	32"	32"	32"	32"	32"
Rear Door	SINGLE / RAMP	SINGLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP	DOUBLE / RAMP
Sand Pad	STD	STD	STD	STD	STD	STD	STD
Crossmembers	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES	YES	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive	Automotive

For V-Nose Dimensions Please Refer to the Element Literature

Specifications Subject to Change Without Notice