



# VISION

## 7' & 8.5' Wide

Specifications vary by plant



### STANDARD FEATURES

Optional Equipment May Be Shown

- Tube Main Frame Construction
- 16" O.C. Frame
- 16" O.C. Tube Sidewalls
- 24" O.C. Roof Bows - 7' Wides
- 16" O.C. Roof Bows - 8.5' Wides
- Spring Axles
- EZ-Lube Hubs
- 4-Wheel Electric Brakes
- 15" Radial Tires
- Chrome Plastic Hub Caps
- 2-5/16" Coupler
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- 30" Bullnose (Flat Top)
- Radius Front (Round Top)
- TPO Cap (Round Top)
- .080 Top Wrap (Round Top)
- .030 Screwless Aluminum Exterior
- Polished Corners or Nose
- 1 Piece Aluminum Roof
- Aluminum Fenders on 7' Wide
- Aluminum Fender Flares on 8.5' Wide
- 24" Stoneguard
- Ramp Door w/ Spring Assist or Double Rear Doors
- Side Door w/ Flushlock
- (2) Sidewall Vents
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- (2) LED Side Mount Turn Signals
- (2) LED Dome Lights w/ Switch
- Automotive Undercoating
- Limited 5 Year Warranty

	<b>VISION ROUND TOP</b>				
	<b>VRLC7X14TE2</b>	<b>VRLC7X16TE2</b>	<b>VRLC8.5X20TE2</b>	<b>VRLC8.5X24TE2</b>	<b>VRLC8.5X24TE3</b>
Overall Length	17'7"	19'7"	23'11"	27'10"	27'10"
Width	102"	102"	102"	102"	102"
Height	95"	95"	100"	100"	100"
Interior Length	14'3"	16'3"	20'5"	24'4"	24'4"
Interior Width	81"	81"	96"	96"	96"
Interior Height	72"	72"	78"	78"	78"
Platform Height	21"	21"	21"	21"	21"
Rear Opening Ht.	66 3/4"	66 3/4"	72 3/4"	72 3/4"	72 3/4"
Rear Opening Wd.	76 1/2"	76 1/2"	93 1/2"	93 1/2"	93 1/2"
Hitch Ball Height	19"	19"	19"	19"	19"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Brakes	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
GVWR	7000#	7000#	7000#	7000#	9950#
Hitch Weight	240#	270#	390#	410#	420#
Curb Weight	2000#	2291#	3210#	3680#	3720#
Payload Capacity	5000#	4710#	3790#	3320#	6230#
Tires	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	High Performance	High Performance	High Performance	High Performance	High Performance
Tail Lights	LED	LED	LED	LED	LED
Clearance Lights	LED	LED	LED	LED	LED
Dome Light	2	2	2	2	2
Switch	STD	STD	STD	STD	STD
Sidewall Vents	2	2	2	2	2
Stone Guard	24"	24"	24"	24"	24"
Side Door	32"	32"	36"	36"	36"
Rear Door	DOUBLE/RAMP	DOUBLE/RAMP	DOUBLE/RAMP	DOUBLE/RAMP	DOUBLE/RAMP
Sand Pad	STD	STD	STD	STD	STD
Crossmembers	16" OC	16" OC	16" OC	16" OC	16" OC
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	16" OC	16" OC	16" OC
Axles	SPRING	SPRING	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive	Automotive	Automotive

For V-Nose Dimensions Please Refer to the Element Literature

Specifications Subject to Change Without Notice