



JASPER

Deckover Snowmobile Trailers

Specifications vary by plant
May be shown with optional equipment



Standard Features

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 16" O.C. Roof Bows
- Spring Axles
- 4-Wheel Electric Brakes
- 15" Radial Tires
- 2 5/16" Adjustable Coupler
- Safety Chains
- 5000# Drop Down Leg Jack
- Sand Pad
- 3/4" High Performance Floor
- High Performance Wall Liner
- 12"H Interior Kick Plate
- 1 Piece Aluminum Roof
- 24" Stoneguard
- Ramp Door w/ Spring Assist
- 72" Front Ramp Door w/ Spring Assist
- 36" Entry Door w/ Flushlock
- Steel Slide-out Step
- (1) Fuel Door
- (2) Sidewall Vents
- LED Exterior Lighting
- (2) Dome Lights w/ Switch
- Traction Strips
- Beavertail
- Transport Canada Certified Tie Downs
- Moisture Barrier (UT)
- Automotive Undercoating
- Limited 3 Year Warranty

COMPASS TRAILERS

Manufacturing in TX: 866.622.0858 • AZ: 877.541.5665 • UT: 877.544.5665

| | 8.5X17TE2 | 8.5X21TE2 | 8.5X27TE3 | 8.5X29TE3 |
|-----------------------|------------------|------------------|------------------|------------------|
| Overall Length | 20' | 24' | 30' | 32' |
| Width | 100" | 100" | 100" | 100" |
| Height | 9'3" | 9'3" | 9'4" | 9'4" |
| Interior Length | 16' | 20' | 26' | 28' |
| Interior Width | 96" | 96" | 96" | 96" |
| Interior Height | 78" | 78" | 78" | 78" |
| Platform Height | 31" | 31" | 31" | 31" |
| Rear Opening Height | 75" | 75" | 75" | 75" |
| Rear Opening Width | 93 1/2" | 93 1/2" | 93 1/2" | 93 1/2" |
| Hitch Ball Height | ADJ | ADJ | ADJ | ADJ |
| Hitch Ball Size | 2 5/16" | 2 5/16" | 2 5/16" | 2 5/16" |
| Frt Ramp Open. Height | 68 1/2" | 68 1/2" | 68 1/2" | 68 1/2" |
| Frt Ramp Open. Width | 72" | 72" | 72" | 72" |
| Brakes | ELECTRIC | ELECTRIC | ELECTRIC | ELECTRIC |
| GVWR | 7000# | 7000# | 9900# | 9900# |
| Curb Weight | 3170# | 3750# | 4070# | 4280# |
| Payload Capacity | 3830# | 3250# | 5830# | 5620# |
| Tires | 15" | 15" | 15" | 15" |
| Wheels | E-COAT | E-COAT | E-COAT | E-COAT |
| Frame | TUBE | TUBE | TUBE | TUBE |
| Floor | 3/4" | 3/4" | 3/4" | 3/4" |
| Sidewalls | High Performance | High Performance | High Performance | High Performance |
| Tail Lights | LED | LED | LED | LED |
| Clearance Lights | LED | LED | LED | LED |
| Dome Light | 2 | 2 | 2 | 2 |
| Switch | STD | STD | STD | STD |
| Sidewall Vents | 2 | 2 | 2 | 2 |
| Stone Guard | 24" | 24" | 24" | 24" |
| V-Nose | STD | STD | STD | STD |
| Side Door | 36" | 36" | 36" | 36" |
| Tie Downs | STD | STD | STD | STD |
| Beavertail | STD | STD | STD | STD |
| Sand Pad | STD | STD | STD | STD |
| Crossmembers | 24" OC | 24" OC | 24" OC | 24" OC |
| Side Posts | 16" OC | 16" OC | 16" OC | 16" OC |
| Roof Bows | 16" OC | 16" OC | 16" OC | 16" OC |
| Axles | SPRING | SPRING | SPRING | SPRING |
| EZ Lube | YES | YES | YES | YES |
| Traction Strips | STD | STD | STD | STD |
| Undercoat | Automotive | Automotive | Automotive | Automotive |

Specifications Subject to Change Without Notice